

	<p align="center">P.H.P.U. IZOL PLAST Sp. z o.o. 44-362 Rogów ul. Raciborska 79 tel./fax 32-4512444, 32-4512010 www.izol-plast.rogow.pl</p>	<p align="center">INDEX CARD</p> <p align="center">A set of flexible cabling with insulated screws for connecting SBS-4 accumulator batteries</p>
---	---	---



Application:

The **cabling set** is designed to connect the power units of the SBS-4 flameproof battery boxes.

Construction

Connectors are made of a single wire with a cross-section of 35mm² or 70mm² with rubber insulation made of flame-retardant rubber.

1. The ends and connection points of the connectors are pressed in copper sleeves.
2. Mounting holes are drilled in the pressed ends.
3. The pressed ends of the rails are insulated with rubber.

The **wiring set** includes the following connectors:

- | | | |
|----|---|--------------------------|
| a) | flexible connector L 130mm, 35mm ² - | 103 pcs. |
| b) | flexible connector L 160 mm, 35mm ² - | 24 pcs. |
| c) | flexible connector L 300mm, 35mm ² - | 8 pcs. |
| d) | flexible connector L 500mm, 70mm ² - | 1 piece |
| e) | flexible connector L 600mm, 70mm ² - | 3 pcs. |
| f) | flexible connector L 1450mm +L 800, 70mm ² - | 1 piece – (36 V) |
| g) | flexible connector L 800mm, 70mm ² - | 1 piece – (26 V) |
| h) | flexible connector L 1450, 70mm ² - | 2 pcs. (for 36V – 1pcs.) |
| i) | M10 bolts with test holes - | 288 pcs. |
| j) | special copper sleeve 70mm ² - | 1 piece |
| k) | Scotch tape 23 (4,5 m) | 1 piece |
| l) | type E silpasta- | 0,5 kg |

On request, we also make connectors of a different length, e.g.

Flexible connector L 210mm, 35mm²

Double flexible connector ŁP 2100mm, 70mm²