



ISO

9001
OBAC/002/SZJ/20

P.H.P.U.
IZOL PLAST

Sp. z o.o.
44-362 Rogów
ul. Raciborska 79
tel./fax 32-4512444,
32-4512010
www.izol-plast.rogow.pl

INDEX CARD

**The standoff insulator type WZ-75
is intended for installation in the
junction boxes of 6 kV motors**



Application:

The WZ-75 type standoff insulator is intended for installation in 6 kV motor junction boxes.
Rated voltage: U_n 6 kV

The insulator is made of electrotechnical porcelain, type: C 130

The insulator porcelain was made in accordance with the technical documentation NF 7375, while maintaining the Quality Management System.

Technical data of the WZ-75 insulator

Rated voltage U_n

6 [kV]

Weight

~0,65 [kg]

Dimensions

125xØ76 [mm]

Nominal diameter of the clamps

M10 (or M12)

16 [Nm]

Maximum torque acting on the terminal [Nm]



ISO

9001
OBAC/002/SZJ/20

P.H.P.U.

IZOL PLAST

Sp. z o.o.
44-362 Rogów
ul. Raciborska 79
tel./fax 32-4512444,
32-4512010
www.izol-plast.rogow.pl

INDEX CARD

**The standoff insulator type WZ-75
is intended for installation in the
junction boxes of 6 kV motors**