



ISO

9001  
OBAC/002/SZJ/23

P.H.P.U.  
**IZOL PLAST**

Sp. z o.o.  
44-362 Rogów  
ul. Raciborska 79  
tel./fax 32-4512444,  
32-4512010  
[www.izol-plast.rogow.pl](http://www.izol-plast.rogow.pl)

## INDEX CARD

**The standoff insulator type WZ-75  
is intended for installation in the  
junction boxes of 6 kV motors**



### Application:

The WZ-75 type standoff insulator is intended for installation in 6 kV motor junction boxes.

Rated voltage:  $U_n$  6 kV

The insulator is made of electrotechnical porcelain, type: C 130

The insulator porcelain was made in accordance with the technical documentation NF 7375, while maintaining the Quality Management System.

### Technical data of the WZ-75 insulator

Rated voltage  $U_N$

6 [kV]

Weight

~0,65 [kg]

Dimensions

125xØ76 [mm]

Nominal diameter of the clamps

M10 (or M12)

Maximum torque acting on the terminal [Nm]

16 [Nm]



ISO

9001  
OBAC/002/SZJ/23

P.H.P.U.

**IZOL PLAST**

Sp. z o.o.  
44-362 Rogów  
ul. Raciborska 79  
tel./fax 32-4512444,  
32-4512010  
[www.izol-plast.rogow.pl](http://www.izol-plast.rogow.pl)

## INDEX CARD

**The standoff insulator type WZ-75  
is intended for installation in the  
junction boxes of 6 kV motors**