

 <p><b>ISO 9001</b> OBAC/002/SZJ/23</p>	<p><b>P.H.P.U.</b> <b>IZOL PLAST</b> Sp. z o.o. 44-362 Rogów ul. Raciborska 79 tel./fax 32-4512444, 32-4512010 <a href="http://www.izol-plast.rogow.pl">www.izol-plast.rogow.pl</a></p>	<p><b>INDEX CARD</b></p> <p><b>A set of flexible cabling with insulated screws for connecting SBS-5pcs rechargeable batteries</b></p>
------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------



#### Application:

The **cabling set** is designed to connect the power units of the SBS-5 flameproof battery boxes.

#### Construction

**Connectors** are made of a single wire with a cross-section of 35 mm<sup>2</sup> or 70 mm<sup>2</sup> with rubber insulation made of flame-retardant rubber.

1. The ends and connection points of the connectors are pressed in copper sleeves.
2. Mounting holes are drilled in the pressed ends.
3. The pressed ends of the rails are insulated with rubber.

The wiring set includes the following connectors:

- |    |                                                  |          |
|----|--------------------------------------------------|----------|
| a) | Flexible connector L 130mm, 35mm <sup>2</sup> -  | 52 pcs.  |
| b) | Flexible connector L 160mm, 35mm <sup>2</sup> -  | 24 pcs.  |
| c) | Flexible connector L 230mm, 35mm <sup>2</sup> -  | 4 pcs.   |
| d) | Flexible connector L 600mm, 70mm <sup>2</sup> -  | 1 piece  |
| e) | Flexible connector L 800mm, 70mm <sup>2</sup> -  | 1 piece  |
| f) | Flexible connector L 1700mm, 70mm <sup>2</sup> - | 2 pcs.   |
| g) | M10 screws with measuring holes -                | 168 pcs. |
| h) | Silpasta type E-                                 | 0,5 kg   |